

Polishing machine for bent pipes and straight pipes



Made in Italy



ART.
78

SATINATRICE - LEVGATRICE "PLANETARIA"

"PLANETARY" SATINING - BELT GRINDING MACHINE

MACHINE À SATINER - PONCEUSE À BANDES "PLANÉTAIRES"

"PLANETARISCHE" SATINIERMASCHINE - BANDSCHLEIFMASCHINE



G

E

F

G1




Volt 400 kW 0,75

hp	Rpm	m/s	E	F	G	G1	dB	kg
1	1500	7	540	665	1223	940	85	90

B









OPTIONAL

A	B	Ø mm	R min	IA-1
280	11	Min 4 - 20 Max	40	kW 0,55

General technical info

Power supply	400 50 3	Volt Hz Phase
Abrasive belt motor power	0,75 (1,0)	kW (hp)
Motor speed	1400	rpm
Peripheral speed	7	m/sec
Abrasive belt dimension (wide x length)	(2x) 10 x 280	mm
Overall dimension (Width x Depth x Height)	540 x 665 x H. 1223	mm
Acoustic emission	85	dB
Weight standard machine	360	kg
Dust extraction connection	ø 43	mm
Stations	1	No.
Workpiece diameter allowed	ø 3 ÷ ø 20	mm
Minimum radius bend pipe	R. 40	mm

Standard Equipments



Machine respect CE stamp of compliance

- Machine with CE conformity mark made respecting the requirements of the most recent directives concerning it.
- Machine complete with instruction manual complete with CE conformity certificate, test sheet and exploded view with relative spare parts list.
- Machine equipped with a set of service keys suitable for the adjustment and maintenance of the machine.



Guarantee of European standards

The stringent tests guarantee that all the requisites and standards necessary to obtain the guarantee in accordance with European standards are respected. Since the project we dedicate a lot of care and attention to making the machine with high quality level to deliver machines that last over time.

Technical general information

- Right / left support for supporting details.
- Spring device for automatic tube diameter adjustment.
- Spring device for quick replacement of abrasive belts.
- Double sanding belt 11x280 mounted on the machine ready to use.
- Possibility of mounting scotch-brite belts.
- Carter sander with predisposition for connection of suction system Ø45mm.

Optional Equipments



cod. IA-1: DUST EXTRACTOR - ONE CONNECTION

DUST EXTRACTOR kit with one suction mouth: complete of dust filter bag in flexible aluminum pipe and hose clamps. The extractor is mounted inside the base and wired to the electrical panel. TECHNICAL FEATURES- Motor: Volt 400 - Rpm 2800 - kW 0,55- Max flow rate: 1.000 m3 / h- Max total pressure: 85 mm H2O

Technical modification

This product data sheet does not constitute a contractual obligation.

We reserve the right to modify and/or improve our machines without prior notice.

Some photographs and illustrations are purely demonstrative and may differ from the real ones.