

Belt grinding machine



Made in Italy



General technical info

Power supply	400 50 3	Volt Hz Phase
Motor power	1,1 (1,5)	kW (hp)
Motor speed	2800	rpm
Acoustic emission	70	dB
Overall dimension (Width x Depth x Height)	600 x 550 x H. 640	mm
Weight standard machine	34	kg

• Belt grinder unit

Abrasive belt dimension (wide x length)	100 x 1000	mm
Peripheral speed	15	m/sec
Dimension of working plane (behind abrasive belt)	100 x 290	mm
Driving wheel dimension	100	mm
Orientable belt grinding arm	0 ÷ 90	°

• Polisher - Buffer unit

Brush maximum external size	ø 200	mm
Brush minimum hole size	ø 20	mm
Motor shaft diameter	ø 20	mm
Brush maximum wide size	50	mm
Peripheral speed of brush	30	m/sec

Standard Equipments



Machine respect CE stamp of compliance

- Machine with CE conformity mark made respecting the requirements of the most recent directives concerning it.
- Machine complete with instruction manual complete with CE conformity certificate, test sheet and exploded view with relative spare parts list.
- Machine equipped with a set of service keys suitable for the adjustment and maintenance of the machine.



Guarantee of European standards

The stringent tests guarantee that all the requisites and standards necessary to obtain the guarantee in accordance with European standards are respected. Since the project we dedicate a lot of care and attention to making the machine with high quality level to deliver machines that last over time.

Base

Stable bench structure with anti-vibration rubbers at the base.

Electrical panel

Electric controls with emergency stop and anti-reset function for accidental starting and electronic overload protection.

Orientable arm sander

Arm sander adjustable from 0 ° to 90 ° and intermediate positions.

Type of work

Three types of processing, in plan with support, on tyred wheel, on tyred wheel with support.

Work surface

Behind the abrasive tape has a durable floor in abutment replaceable steel over time.

Rubberized grooved wheel

Rubberized, grooved and balanced drive wheel for better drag of the abrasive belt.

Abrasive belt

Abrasive belt mounted on the machine ready for use.

Belt grinder cover

Carter sander with predisposition connection system.

Locking accessories

Locking and reducing steel flange for grinding wheel with spacers and clamping nuts.

Support

Plan special adjustable support according to the diameter of the grinding wheel.

Grinding wheel

Machine predisposed to mount the grinding wheel.Grinding wheel not included.

Grinder cover

Cover with predisposition connection system with predisposition connection system.

Anti-spark repair

Transparent protection arrester with friction joint.

Optional Equipments



cod. **BAS.02: MACHINE STAND**

Strong stand with anti-vibration rubber and inside a useful space for tools. Dimensions 300X200 X H.750 - KG 25



cod. **BAS.02+IA-2: MACHINE STAND WITH DUST EXTRACTION TWO CONNECTIONS**

Stand with dust extractor kit with two suction mouth: complete of dust filter bag in flexible aluminum pipe and hose clamps. The extractor is wired to the electrical panel. TECHNICAL FEATURES- Motor: Volt 400 - Rpm 2800 - kW 0,55- Max flow rate: 1.000 m³ / h- Max total pressure: 85 mm H₂O



cod. **M2V-TA: TWO SPEEDS MOTOR**

Two speeds three-phase motor Rpm 1400/2800, recommended for use with stainless steel and aluminum. 400 volts - 50 Hz - 3 phase



cod. **INV-MF: VARIABLE SPEEDS SINGLE PHASE**

Single-phase inverter for electronic regulation of motor revolutions from 300 ÷ 3000 Rpm. The inverter is supplied inside box for the dust protection, which can be controlled with potentiometer. Motor with maximum power 1,1 kW.

Technical modification

This product data sheet does not constitute a contractual obligation.

We reserve the right to modify and/or improve our machines without prior notice.

Some photographs and illustrations are purely demonstrative and may differ from the real ones.