


Belt grinding machine



Made in Italy



ART. 87		LEVIGATRICE ORIENTABILE A NASTRO ORIENTABLE BELT GRINDING MACHINE TANK BANDSCHLEIFMASCHINE									
											
Volt 400 kW 1,1		dB		F	E	G	G1	kg			
1,5	Rpm 2800	m/s 30	68	450	750	1330	970	55			
						OPTIONALS					
											
						Volt 230/1F					
						INV.MF		IA-1			
1250		50		300		60		Ø200x50xØ20		Rpm 0÷3000	
										kW 0,55	

General technical info

Power supply	400 50 3	Volt Hz Phase
Motor power	1,1 (1,5)	kW (hp)
Motor speed	2800	rpm
Acoustic emission	68	dB
Overall dimension (Width x Depth x Height)	450 x 750 x H. 1330	mm
Weight standard machine	55	kg

• Belt grinder unit - wheel processing

Abrasive belt dimension (wide x length)	50 x 1250	mm
Peripheral speed	30	m/sec
Dimension of working plane (behind abrasive belt)	60 x 300	mm
Dimensions of grooved rubberized driving wheel (wide x diameter)	50 x ø 200	mm
Orientable belt grinding arm	0 ÷ 90	°

Standard Equipments



Machine respect CE stamp of compliance

- Machine with CE conformity mark made respecting the requirements of the most recent directives concerning it.
- Machine complete with instruction manual complete with CE conformity certificate, test sheet and exploded view with relative spare parts list.
- Machine equipped with a set of service keys suitable for the adjustment and maintenance of the machine.



Guarantee of European standards

The stringent tests guarantee that all the requisites and standards necessary to obtain the guarantee in accordance with European standards are respected. Since the project we dedicate a lot of care and attention to making the machine with high quality level to deliver machines that last over time.

Base

Strong base with anti-vibration rubbers at the base and a useful shelf for tools inside.

Electrical panel

Low voltage electric controls with padlock device integrated in the main electric switch.

Orientable arm sander

Arm sander adjustable from 0 ° to 90 ° and intermediate positions.

Work surface

Behind the abrasive tape has a durable floor in abutment replaceable steel over time.

Rubberized grooved wheel

Rubberized, grooved and balanced drive wheel for better drag of the abrasive belt.

Abrasive belt

Abrasive belt mounted on the machine ready for use.

Belt grinder cover


Carter sander with predisposition connection system.

Optional Equipments




cod. **IA-1**: **DUST EXTRACTOR - ONE CONNECTION**

DUST EXTRACTOR kit with one suction mouth: complete of dust filter bag in flexible aluminum pipe and hose clamps. The extractor is mounted outside the base and wired to the electrical panel. TECHNICAL FEATURES- Motor: Volt 400 - Rpm 2800 - kW 0,55- Max flow rate: 1.000 m³ / h- Max total pressure: 85 mm H₂O



cod. **M1V-MF**: **SINGLE PHASE MOTOR ONE SPEED**

Single phase motor one speed Rpm 2800 230 volts - 50 Hz - 1 phase



cod. **M2V-MF**: **TWO SPEEDS SINGLE PHASE MOTOR**

Two speeds single phase motor Rpm 1400/2800 230 volts - 50 Hz - 1 phase



cod. **M2V-TA**: **TWO SPEEDS MOTOR**

Two speeds three-phase motor Rpm 1400/2800, recommended for use with stainless steel and aluminum. 400 volts - 50 Hz - 3 phase



cod. **INV-MF**: **VARIABLE SPEEDS SINGLE PHASE**

Single-phase inverter for electronic regulation of motor revolutions from 300 ÷ 3000 Rpm. The inverter is supplied inside box for the dust protection, which can be controlled with potentiometer. Motor with maximum power 1,1 kW.

Technical modification

This product data sheet does not constitute a contractual obligation.

We reserve the right to modify and/or improve our machines without prior notice.

Some photographs and illustrations are purely demonstrative and may differ from the real ones.