



Belt grinding machine



Made in Italy





General technical info

Power supply	400 50 3	Volt Hz Phase
Motor power	4,5 - 3,7 (6,0 - 5,0)	kW (hp)
Motor speed	2800 - 1400	rpm
Acoustic emission	70	dB
Overall dimension (Width x Depth x Height)	1390 x 720 x H. 1020	mm
Weight standard machine	290	kg

• Belt grinder unit

Abrasive belt dimension (wide x length)	300 x 2500	mm
Peripheral speed	30 - 15	m/sec
Dimension of working plane (behind abrasive belt)	300 x 900	mm
Driving wheel dimension	ø 200	mm
Orientable belt grinding arm	0	°

Standard Equipments



Machine respect CE stamp of compliance

- Machine with CE conformity mark made respecting the requirements of the most recent directives concerning it.
- Machine complete with instruction manual complete with CE conformity certificate, test sheet and exploded view with relative spare parts list.
- Machine equipped with a set of service keys suitable for the adjustment and maintenance of the machine.



Guarantee of European standards

The stringent tests guarantee that all the requisites and standards necessary to obtain the guarantee in accordance with European standards are respected. Since the project we dedicate a lot of care and attention to making the machine with high quality level to deliver machines that last over time.

Base

Strong base with anti-vibration rubbers at the base and a useful shelf for tools inside.

Electrical panel

Low voltage electric controls with padlock device integrated in the main electric switch.

Electronic brake card

Emergency stop with electronic motor braking with safety anti-reset function.

Motor

Motor 2 speeds

Arm sander

Belt sander in horizontal position.

Rubberized grooved wheel

Rubberized, grooved and balanced drive wheel for better drag of the abrasive belt.

Work surface

Behind the abrasive tape has a durable floor in abutment replaceable steel over time.

Wheel processing

Ability to work in the vicinity of the wheel with a large contact surface.

Abrasive belt

Abrasive belt mounted on the machine ready for use.

Belt grinder cover

Carter sander with predisposition connection system.

Technical modification

This product data sheet does not constitute a contractual obligation.
We reserve the right to modify and/or improve our machines without prior notice.
Some photographs and illustrations are purely demonstrative and may differ from the real ones.