

Disc grinding machine



Made in Italy



ART. 62		LEVIGATRICE A DISCO GRINDING DISK-MACHINE LAPIDARE TELLERSCHLEIFMASCHINE												
														
Volt 400 kW 3														
hp	Rpm	m/s	dB	E	F	G	G1	kg						
4	950	30	68	700	800	1360	900	135						
														
		OPTIONAL												
Ø	M	N	J°	IA-1										
600	650	230	0°-90°	kW 0.55										

0°-90°

General technical info

Power supply	400 50 3	Volt Hz Phase
Motor power	3,0 (4,0)	kW (hp)
Motor speed	950	rpm
Acoustic emission	68	dB
Overall dimension (Width x Depth x Height)	800 x 700 x H. 1360	mm
Weight standard machine	135	kg

• Abrasive disc grinder unit

Abrasive disc dimension	ø 600	mm
Peripheral speed	30	m/sec
Support table dimension	650 x 230	mm
Support table revolution	0 ÷ 90	°

Standard Equipments



Machine respect CE stamp of compliance

- Machine with CE conformity mark made respecting the requirements of the most recent directives concerning it.
- Machine complete with instruction manual complete with CE conformity certificate, test sheet and exploded view with relative spare parts list.
- Machine equipped with a set of service keys suitable for the adjustment and maintenance of the machine.



Guarantee of European standards

The stringent tests guarantee that all the requisites and standards necessary to obtain the guarantee in accordance with European standards are respected. Since the project we dedicate a lot of care and attention to making the machine with high quality level to deliver machines that last over time.

Base

Strong base with anti-vibration rubbers at the base and a useful shelf for tools inside.

Electrical panel

Low voltage electric controls with padlock device integrated in the main electric switch.

Electronic brake card

Emergency stop with electronic motor braking with safety anti-reset function.

Support plane

Support plane details inclinable with adjustable height.

Disc

Aluminium disc perfectly balanced.

Abrasive disc

Abrasive disc mounted on the machine ready for use.

Belt grinder cover

Carter sander with predisposition connection system.

Anti-spark repair

Transparent protection arrester with friction joint.

Optional Equipments



cod. IA-1: DUST EXTRACTOR - ONE CONNECTION

DUST EXTRACTOR kit with one suction mouth: complete of dust filter bag in flexible aluminum pipe and hose clamps. The extractor is mounted inside the base and wired to the electrical panel. TECHNICAL FEATURES- Motor: Volt 400 - Rpm 2800 - kW 0,55- Max flow rate: 1.000 m³ / h- Max total pressure: 85 mm H₂O

Technical modification

This product data sheet does not constitute a contractual obligation.

We reserve the right to modify and/or improve our machines without prior notice.

Some photographs and illustrations are purely demonstrative and may differ from the real ones.