

Polishing machine



Made in Italy



ART. 27		PULTRICE DOPPIA DOUBLE POLISHING MACHINE POLISSOIR (2 POSTES) DOPPELSCHLEIF-UND POLIERMASCHINE									
											
Volt 400 kW 1,8											
hp	Rpm	m/s	dB	E	F	G1	L	kg			
2,5	1400 2800	18 36	70	600	1000	910	300	85			
											
NOT INCLUDED		OPTIONAL		OPTIONAL							
Ø mm		INVERTER		IA-2							
Ø250xØ25		Rpm 0÷3000		kW 0,55							

General technical info

Power supply	400 50 3	Volt Hz Phase
Motor power	1,9 - 1,1 (2,5 - 1,5)	kW (hp)
Motor speed	2800 - 1400	rpm
Acoustic emission	70	dB
Overall dimension (Width x Depth x Height)	1000 x 600 x H. 910	mm
Weight standard machine	85	kg

• Polisher - Buffer unit

Brush maximum external size	ø 250	mm
Motor shaft diameter	ø 25	mm
Brush maximum wide size	70	mm
Peripheral speed	36 - 18	m/sec
Operators	1	No.
Stations	2	No.

Standard Equipments



Machine respect CE stamp of compliance

- Machine with CE conformity mark made respecting the requirements of the most recent directives concerning it.
- Machine complete with instruction manual complete with CE conformity certificate, test sheet and exploded view with relative spare parts list.
- Machine equipped with a set of service keys suitable for the adjustment and maintenance of the machine.



Guarantee of European standards

The stringent tests guarantee that all the requisites and standards necessary to obtain the guarantee in accordance with European standards are respected. Since the project we dedicate a lot of care and attention to making the machine with high quality level to deliver machines that last over time.

Base

Strong base with anti-vibration rubbers at the base and a useful shelf for tools inside.

Electrical panel

Low voltage electric controls with padlock device integrated in the main electric switch.

Electronic brake card

Emergency stop with electronic motor braking with safety anti-reset function.

Motor

Motor 2 speeds

Polishing cover

Carter adjustable for a comfortable and precise positioning of the operator and with predisposition connection system.

Locking accessories

Locking and reducing steel flange for brush, flap wheel with spacers and clamping nuts.

Anti-spark repair

Transparent protection arrester with friction joint.

Optional Equipments



cod. **IA-2: DUST EXTRACTOR - TWO CONNECTIONS**

DUST EXTRACTOR kit with two suction mouth: complete of dust filter bag in flexible aluminum pipes and hose clamps. The extractor is mounted inside the base and wired to the electrical panel. TECHNICAL FEATURES- Motor: Volt 400 - Rpm 2800 - kW 0,55- Max flow rate: 1.000 m³ / h- Max total pressure: 85 mm H₂O

Technical modification

This product data sheet does not constitute a contractual obligation.

We reserve the right to modify and/or improve our machines without prior notice.

Some photographs and illustrations are purely demonstrative and may differ from the real ones.