

Polishing machine



Made in Italy



		PULTRICE SOSPESA PROFESSIONAL PROFESSIONAL SUSPENDED POLISHING MACHINE POLISSEUR SUSPENDUE PROFESSIONNEL BERUFICHE HÄNGEND POLIERMASCHINE									
											
Volt 400 kW 5.5		NOT INCLUDED		OPTIONAL		OPTIONAL		OPTIONAL		OPTIONAL	
hp	Rpm	m/s	E	F	G1	L	dB	kg	Ø mm	Rpm	INVERTER
7.5	1450	28	1450	1500	1500	1500	70	425	Ø400x325	700-1400	INVERTER
	2800	28								Rpm 0-2000	ASP.01

General technical info

Power supply	400 50 3	Volt Hz Phase
Motor power	7,2 - 5,3 (9,8 - 7)	kW (hp)
Motor speed	2800 - 1400	rpm
Acoustic emission	70	dB
Overall dimension (Width x Depth x Height)	1050 x 1450 x H. 430 ÷ 1500	mm
Weight standard machine	425	kg

• Polisher - Buffer unit

Brush maximum external size	ø 400	mm
Motor shaft diameter	ø 35	mm
Brush maximum wide size	75	mm
Peripheral speed	58 - 29	m/sec

Standard Equipments



Machine respect CE stamp of compliance

- Machine with CE conformity mark made respecting the requirements of the most recent directives concerning it.
- Machine complete with instruction manual complete with CE conformity certificate, test sheet and exploded view with relative spare parts list.
- Machine equipped with a set of service keys suitable for the adjustment and maintenance of the machine.



Guarantee of European standards

The stringent tests guarantee that all the requisites and standards necessary to obtain the guarantee in accordance with European standards are respected. Since the project we dedicate a lot of care and attention to making the machine with high quality level to deliver machines that last over time.

Electrical panel

Low voltage electric controls with padlock device integrated in the main electric switch.

Electronic brake card

Emergency stop with electronic motor braking with safety anti-reset function.

Motor

Motor 2 speeds

Polishing cover

Carter adjustable for a comfortable and precise positioning of the operator and with predisposition connection system.

Locking accessories

Locking and reducing steel flange for brush, flap wheel with spacers and clamping nuts.

Anti-spark repair

Transparent protection arrester with friction joint.

Technical modification

This product data sheet does not constitute a contractual obligation.
We reserve the right to modify and/or improve our machines without prior notice.
Some photographs and illustrations are purely demonstrative and may differ from the real ones.