



Made in Italy



ASP. 04		ASPIRATORE CENTRIFUGO CON BASAMENTO BAG FILTER DUST EXTRACTOR WITH BASE VENTILATEUR D'ASPIRATION CENTRIFUGE AVEC SOCLE ABSAUGANLAGE IM UNTERSCHRANK EINGEBAUT					
							
Volt 400 kW 0,55							
hp	Rpm	dB	E	F	G	G1	kg
0,75	2800	70	600	600	780	530	45
Portata max m³/h			Pressione totale max mm H₂O				
1000			85				

General technical info

Power supply	400 50 3	Volt Hz Phase
Motor power	0,55 (0,75)	kW (hp)
Motor speed	2800	rpm
Acoustic emission	70	dB
Overall dimension (Width x Depth x Height)	600 x 600 x H. 780	mm
Weight standard machine	45	kg

• Dust extractor

Max air flow	1000	m³/h
Max water lift	85	mmH2O
Inlet Ø	80	mm

Standard Equipments



Machine respect CE stamp of compliance

- Machine with CE conformity mark made respecting the requirements of the most recent directives concerning it.
- Machine complete with instruction manual complete with CE conformity certificate, test sheet and exploded view with relative spare parts list.
- Machine equipped with a set of service keys suitable for the adjustment and maintenance of the machine.



Guarantee of European standards

The stringent tests guarantee that all the requisites and standards necessary to obtain the guarantee in accordance with European standards are respected. Since the project we dedicate a lot of care and attention to making the machine with high quality level to deliver machines that last over time.

Electrical panel

Electric controls with emergency stop and anti-reset function for accidental starting and electronic overload protection.

Structure of dust extractor

Structure adapted to channel the dust emery.

Bag filter

Fireproof bag filter.

Technical modification

This product data sheet does not constitute a contractual obligation.

We reserve the right to modify and/or improve our machines without prior notice.

Some photographs and illustrations are purely demonstrative and may differ from the real ones.